

# TIME ATTENDANCE & ACCESS CONTROL



## CARD



**CME1000**

## FINGERPRINT



**CME1000F**

### PRODUCT FEATURES:

- Touch Screen
- Optical /Capacitive Sensor
- 2 USB Port POE
- Optional Wifi,GSM/GPRS modem
- 10hrs Battery back up



### Technical specifications

Keypad	1 key with blue led
Display	Display TFT 7" 16:9 800x480, LED backlit, touch screen
Integrated Readers	Internal RFID reader in any of the technologies supported by AXESS TMC <ul style="list-style-type: none"> <li>• 125KHz EM4102 compatibles (dual - head)</li> <li>• 125KHz HID</li> <li>• 13.56MHz multi-standard R&amp;W ISO14443/15693 (with Mifare)</li> <li>• 13.56MHz Legic advant muti-standard hi-security R&amp;W ISO14443/15693</li> </ul>
Auxilliary Readers	<ul style="list-style-type: none"> <li>• Optional external readers: magnetic or barcode swipe readers - RJ11 for pen or barcode scanner</li> <li>• Optional external biometric reader with optical or capacitive sensor - 9500 templates 1:N (recommends up to 1000 users in identification mode)1:1 with templates on terminal's memory or on RFID card</li> </ul>
Communication Ports	<ul style="list-style-type: none"> <li>• 2 USB 1.1 host ports</li> <li>• 1 x Ethernet 10/100 Power Over Ethernet A&amp;B compliant</li> <li>• 1 x Serial RS232 optocoupled</li> <li>• 1 x RS485 (NET92 master protocol can be enabled)</li> </ul> Options <ul style="list-style-type: none"> <li>• WiFi 802.11 b/g (USB)</li> <li>• GSM / GPRS modem (USB)</li> <li>• Memory Key (USB)</li> <li>• PSTN 56K analog modem</li> </ul>
Input/Output	2 x Relays 1A 30V configurable: Normally Open or Normally Closed 2 x Digital optocoupled inputs for dry contacts
Power Supply	12....48 VDC 5...7W (up to 10W during fast battery charge)
Battery	Backup battery: 2 versions: 2 h or 10 h continued operation in case of power failure
Physical Characteristics	<ul style="list-style-type: none"> <li>• Casing: ABS V0, auto-extinguish, IP55</li> <li>• Dimensions: 132x232x52 mm (HxLxW)</li> <li>• Weight: 1 Kg</li> </ul> Vertical or horizontal mounting
Audio & Video	1W Mono Speaker with wav and mp3 playback capabilities Microphone for recording functions
Operating System/Other Services	Compact .NET framework 2.0 FTP server, Web server IE6 compliant jscript and vbscript Telnet - Remote desktop client Internet browser (also integrated in internal T&A application)
Memory	64 Mbyte RAM and 64 MBflash (30 MB available as internal flash disk expandable to GBs -with USB Keyfob)



### CARDZ MIDDLE EAST

PO Box: 95781, Office 106 Al Nasa Building Al Maktoum Road  
Deira, Dubai UAE, Tel: +971 4 2293780 Fax: +971 4 2293790  
Email: sales@cardzme.com, Web: www.cardzme.com