

Protégé® EliteSuite® Touchscreen Keypad



The Protégé® EliteSuite® Touchscreen Keypad is the ideal solution to creating an outstanding user experience. Eliminate the need for a myriad of keypads, control panels and switches for each part of a system create true integration in any building environment.

The Protégé® EliteSuite® Touchscreen Keypad is the ideal solution to creating an outstanding user experience. Eliminate the need for a myriad of keypads, control panels and switches for each part of a system create true integration in any building environment:

- 12VDC power supply input with Intelligent Power Saving mode
- Communication with the Protégé® EliteSuite® Integrated System Controller by Ethernet.
- 2 monitored zone inputs or 4 with duplex zone operation
- 1 programmable open collector Output, suitable for digital or relay control.
- 10/100 Ethernet with link/data status indicator
- 128MB onboard RAM, 256MB flash storage space

Mounting Options

With a thickness of only 22mm, the Protégé® EliteSuite® Touchscreen Keypad complements any building interior. The keypad can be mounted over a traditional flush box mount requiring only 15mm depth inside the wall cavity. The widescreen unit complements and enhances any building interior, with custom frame inserts available on special order to truly synchronize interior designs.

Installation Wiring

The power is provided to the Protégé® EliteSuite® Touchscreen Keypad via a suitable 12VDC power supply. Ethernet connection to LAN allows for installation using either a dedicated Protégé® network (recommended for multiple touchscreen installations) or simply connecting the Protégé® EliteSuite® Touchscreen Keypad and Protégé® EliteSuite® Integrated System Controller into the buildings existing network.

Networking Capabilities

The 10/100 Ethernet network connection is completely configurable via the onboard setup menu or the touchscreen builder software.

Apartment Condominium Control

Operating in the Condominium Control mode the Protégé® EliteSuite® Touchscreen Keypad provides a complete standalone 4 zone, 8 user local alarm system:

- Operates autonomously when communication fails without the need for an Protégé® EliteSuite® Integrated System Controller.
- Locally program Siren, Entry and Exit Delay timers and configure the operation of up to 8 users with arming and disarming options.
- 4 zones (zone duplex) can be used for Delay, Instant, Follow, Fire, Fire Delay and 24 Hour Operation.



Integrated Control Technology Limited
 11 Canaveral Drive, Albany, North Shore City 0632, Auckland, New Zealand
 P.O. Box 302-340, North Harbour, Auckland, New Zealand
 Phone: +64 (9) 476 7124
 Fax: +64 (9) 476 7128
 E-mail: support@incontrol.co.nz
 www.integratedcontroltechnology.com

Designers and manufacturers of integrated electronic access control, security and automation products.
 Designed and manufactured by Integrated Control Technology Limited.
 Copyright © Integrated Control Technology Limited 2003-2009. All rights reserved.

Graphics and Video Capabilities

Create a unique user experience with a blend of high quality graphics and customizable images which can be displayed up to 640x480 resolution.

Audio Capabilities

Play high definition audio from WAV, MP3 or WMA files to announce events, warn and inform users of alarm or other input status. Voice notification of network status is built in for ease of installation.

Touchscreen Builder Software

Build a menu system completely customized for each installation. Create pages for the access control, security and automation for any building or combine all key functions into a floor plan or main page.

Technical Specifications	
Operating Voltage	12VDC
Operating Current	490mA, 150mA in Power Save mode
System Memory (RAM)	128MB
Video Memory (RAM)	8MB dedicated graphics cache
Flash Memory	1.8GB flash storage memory
Connectivity (10/100 Ethernet)	Configurable network subsystem
Protégé® RS-485 Network Interface	Proprietary encrypted protocol
Tamper Protection	Adjustable steel tamper tab
Zone Inputs	4
PGM Outputs	1 x 100mA (max)
Operating Temperature	12° to 45°C (41° to 131°F)
Storage Temperature	-10° to 85°C (14° to 185°F)
Humidity	10% to 90% (non condensing)
Dimensions (H x W x D)	125 x 187 x 22mm (4.7 x 3 x 0.75")
Weight	370g (4.16oz)
Specifications are subject to change without notice, please visit www.integratedcontroltechnology.com for updated information.	

Ordering Code	Description
ELT-TLCD	Protégé® EliteSuite® Touchscreen Keypad

Disclaimer:

Whilst every effort has been made to ensure accuracy in the representation of this product, neither Integrated Control Technology Ltd or any employee of the company, shall be liable on any ground whatsoever to any party in respect of decision or actions they may make as a result of using this information. In accordance with the Integrated Control Technology policy of enhanced development, design and specifications are subject to change without notice.

International Compliance Standards:

The Protégé® EliteSuite® Touchscreen Keypad complies with the following international standards. For an installation of the Protégé® EliteSuite® Touchscreen Keypad to comply with any of the standards all installation procedures and programming configuration settings must be made in accordance with the required standard.



ICT CODE: 245-4150-900 V: 90CA